

# 2" Flush Mount Cylinder

## 15W LED Surface Mount (Round or Square)


Catalog #:

Project:

Notes:

Type:

Date:



### STANDARD FINISHES

<b>ABL</b> (Aegean Blue)	<b>PNC</b> (Painted Natural Copper)
<b>BB</b> (Burnished Bronze)	<b>RD</b> (Red)
<b>BK</b> (Gloss Black)	<b>SGR</b> (Sage Green)
<b>BLU</b> (Blue)	<b>SND</b> (Sand)
<b>DVG</b> (Dove Gray)	<b>SS</b> (Satin Silver)
<b>FLG</b> (Flannel Gray)	<b>TBZ</b> (Textured Bronze)
<b>GA</b> (Galvanized)	<b>TGP</b> (Textured Graphite)
<b>GWT</b> (Gloss White)	<b>TNG</b> (Tangerine)
<b>LG</b> (Lime Green)	<b>TTL</b> (Tahitian Teal)
<b>MB</b> (Matte Black)	<b>WT</b> (Semi Gloss White)
<b>MBL</b> (Midnight Blue)	<b>YEL</b> (Yellow)
<b>PNA</b> (Painted Natural Aluminum)	

### Electrical Data

CCT	CRI	Wattage	Source Lumens	Delivered Lumens	Efficacy
2700K	90 CRI	15W	1065lm	821lm	55lpw
3000K	90 CRI	15W	1140lm	880lm	59lpw
3500K	90 CRI	15W	1230lm	947lm	63lpw
4000K	80 CRI	15W	1515lm	1167lm	78lpw

### Multiplier for Delivered Lumens

Wattage	10	15
Multiplier	0.69	1

### Specifications

#### Field Replaceable LED Light Engine

- LED with 2 SDCM binning
- 2700K, 3000K and 3500K at 90 CRI / 4000K at 80 CRI
- 10°, 30°, 50° and 80° optics

#### Field Replaceable Dimming Driver

- Multiple dimming drivers available
- Power factor > 0.9, 50/60Hz

#### Mounting

5" x 1-1/2" canopy included with standard universal dim driver. (7-1/8" x 2-1/4" round canopy or 6-1/4" x 2-1/4" square canopy included with Lutron and eldoLED drivers)

#### Finishes

Available in 22 standard finishes with optional coastal coating to protect finish in coastal environments.

#### Listing / Warranty

- Five (5) year limited warranty
- UL listed to US and Canadian standards for damp locations



### Order Matrix

#### 2" Flush Mount Cylinder (Example: LF2-10-35-10-BK-4-S)

Series	Wattage	CCT / CRI	Optic	Finish	Coastal Coating Option	Rev	Driver	Canopy
<b>LF2</b> (Round)	<b>-10</b>	<b>-27</b> (2700K / 90 CRI)	<b>-10</b>	<b>-ABL</b> (Aegean Blue)	(blank) (No coating)	<b>-4</b>	<b>-S<sup>2</sup></b> (ERP, Universal Dim, Triac/ELV/ 0-10V 10% 120-277V)	(blank) (standard canopy)
<b>SLF2</b> (Square)	<b>-15</b>	<b>-30</b> (3000K / 90 CRI)	<b>-30</b>	<b>-BB</b> (Burnished Bronze)	<b>-C</b> (Coating)		<b>-L1<sup>1</sup></b> (Lutron Hi-lume® 2-Wire 1% 120V) (Lutron EcoSystem® 5% 120-277V)	<b>-CC1<sup>3</sup></b> (Conduit 3-1/4" canopy)
		<b>-35</b> (3500K / 90 CRI)	<b>-50</b>	<b>-BK</b> (Gloss Black)			<b>-L2<sup>1</sup></b> (Lutron Hi-lume® Fade-to-Black 1% 120-277V)	<b>-CC2<sup>3</sup></b> (Conduit 3-7/8" canopy)
		<b>-40</b> (4000K / 80 CRI)	<b>-80</b>	<b>-BLU</b> (Blue)			<b>-L3<sup>1</sup></b> (Lutron Hi-lume® 1% 120-277V)	
				<b>-DVG</b> (Dove Gray)			<b>-EL1<sup>1</sup></b> (eldoLED DALI 1% 120-277V)	
				<b>-FLG</b> (Flannel Gray)			<b>-EL2<sup>1</sup></b> (eldoLED 0-10V 1% 120-277V)	
				<b>-GA</b> (Galvanized)			<b>-DMX<sup>1</sup></b> (DMX 1% 120-277V)	
				<b>-GWT</b> (Gloss White)				
				<b>-LG</b> (Lime Green)				
				<b>-MBL</b> (Midnight Blue)				
				<b>-MB</b> (Matte Black)				
				<b>-PNA</b> (Painted Natural Aluminum)				
				<b>-PNC</b> (Painted Natural Copper)				
				<b>-RD</b> (Red)				
				<b>-SGR</b> (Sage Green)				
				<b>-SND</b> (Sand)				
				<b>-SS</b> (Satin Silver)				
				<b>-TBZ</b> (Textured Bronze)				
				<b>-TGP</b> (Textured Graphite)				
				<b>-TNG</b> (Tangerine)				
				<b>-TTL</b> (Tahitian Teal)				
				<b>-WT</b> (Semi Gloss White)				
				<b>-YEL</b> (Yellow)				

#### Emergency

**EM-1000** (25W LED Remote Inverter)

#### Optic

**EDLM-10-OPTIC-3** (10° Spot)  
**EDLM-30-OPTIC-3** (30° Spot)  
**EDLM-50-OPTIC-3** (50° Spot)  
**EDLM-80-OPTIC-3** (80° Spot)

- Includes larger canopy
- Forward and reverse dimming at 120V only

- CC1 and CC2 only for S driver option

Spec-00222 Revised 12/01/2020

14508 Nelson Ave. City of Industry, CA 91744 • tel: 626.336.4511 • fax: 626.330.4266 • www.csllighting.com  
 ©2020 Creative Systems Lighting, A Division of Troy-CSL Lighting, Inc.  
 All rights reserved. Subject to change without notice.

